





Stand-Alone IIoTA™

DIN Mount IIoTA MiNi™

Engineered by elliTek, In

Part Number	IIOTA-1.0 <i>-xxx</i> *	IIOTA-MiNi-xxx*
Network Interface #1	1000/100/10baseT	1000/100/10baseT
Network Interface #2	100/10baseT	100/10baseT
Network Security	Integrated Hardened Gateway	Integrated Hardened Gateway
Device Connections	0 to 100 (increments of 5)*	0 to 100 (increments of 5)*
Drag & Drop Dashboard Tool	Yes (Licensing Required)	No
Pre-Installed Database Server	Yes - DB2 (Licensing Required)	Yes - MySQL (Included)
Compatible App's (Included)	Workflow Manager Dashboard Designer	Web Server - Apache MySQL Database Server
Power	+5V @ 1.2A, 115/240 VAC	24 Volt @ 0.25A
Case	Cast Aluminum Enclosure	Metal DIN-Style Enclosure
Dimensions WxHxD in/(mm)	7.08" x 7.28" x 3" (180 x 185 x 76)	2.125" x 5.98" x 4.09" (54 x 152 x 104)
Cooling	Passive	Passive
Temperature	-60°C to 80°C	0°C to +70°C
Hardware Warranty	12 months Limited Warranty	12 months Limited Warranty
Certifications	UL, CE	UL, CE
Included in Package	AC power plug, quick start guide	24VDC
* The number of device connections to be specifed in increments of 5 connections and added as a three digit suffix (-xxx) at the time of order (e.g. IIOTA-1.0-015)		

www.elliTek.com